

Single-LED

Distribution by DigiKey



10-2112.1062







10-2112.1062 Single-LED

Loading . . .

Red

330 mcd

	OPER	RATING-	/INDICAT	TION PART
--	------	---------	----------	-----------

Illumination colour:

ELECTRICAL CHARACTERISTICS	
Operating voltage:	24 V AC/DC +10%
Operation current:	7 - 14 mA ±15 %

MECHANICAL CHARACTERISTICS

Weight: 0.001 kg

CERTIFICATE

Lumi. Intensity:

REACH: REACH compliant

RoHS: RoHS compliant

OTHER

Short Description: Single-LED, T5.6, Red, 24 V AC/DC +10%

Hints: For LED element fitting information see Application guidelines, LED polarity

Due to high surface temperatures, the series resistor must not be soldered directly

to the terminals of the equipment (use a terminal plate)

When using AC/DC types with AC operation, slight flickering can occur

The luminous intensity stated is for when used with DC Electrical and optical data are measured at 25 °C

The specified versions are built with a protection diode (halve wave rectifier) in

series and the LED


Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination. The customer has to

decide what resistor shall be used to the LED

Where supply voltages are over 48 V, a voltage-reduction element (external

protective series resistor) must be used.

Wiring diagrams:



Dimension drawings:

