

# Single- LED

10-  
2H13.3164Q

Distribution by  
DigiKey

**DigiKey**



<https://digikey.eao.com/p/10-2H13.3164Q>

Your product:

---



## 10-2H13.3164Q Single-LED

### OPERATING-/INDICATION PART

**Illumination colour:** Yellow

### ELECTRICAL CHARACTERISTICS

**Operating voltage:** 24 - 30 V DC +10%

**Operation current:** 13 - 19 mA  $\pm$ 15 %

**Lumi. Intensity:** 270 - 380 mcd

### MECHANICAL CHARATERISTIC

**Weight:** 0.002 kg

### CERTIFICATE

**REACH:** REACH compliant

**RoHS:** RoHS compliant


### OTHER

**Short Description:** Single-LED, BA9s, Yellow, 24 - 30 V DC +10%


**Kind of illumination:** Single-LED

**Hints:** Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination. The customer has to decide what resistor shall be used to the LED. Electrical and optical data are measured at 25 °C. The specified 12, 24, 28, 48 VAC/DC versions are built with a bridge rectifier

**Wiring diagrams:**



Dimension drawings:



A = (standard)  
 B = (super bright)