

Single-LED

Distribution by DigiKey



10-4H21.1034P







10-4H21.1034P Single-LED

0	PFR	ΔΤΙΝΟ	i-/IND	ICATI	ON	PART

Illumination colour: Yellow

ELECTRICAL CHARACTERISTICS

Operating voltage: 72 V AC/DC

Operation current: 2,2 mA -30%/+25%

Lumi. Intensity: 4 x 112 mcd

MECHANICAL CHARACTERISTICS

Weight: 0.002 kg

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER

Short Description: Single-LED, BA9s, Yellow, 72 V AC/DC

Kind of illlumination: Multi-LED EN 50155

Hints: A suitable LED remover Part No. 700.006.0

The luminous intensity stated is for when used with DC Electrical and optical data are measured at 25 °C


The specified 72 and 110 VAC/VDC versions are built with a bridge rectifier. The specified 72 and 110 VAC/VDC versions are built with a protection diode. In case one LED fails, the other pair of still functioning LED is is working. The light output then is half in order to indicate the malfunction and shows this way the

need for replacement

Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination. The customer has to

decide what resistor shall be used to the LED

Wiring diagrams:



Dimension drawings:

