

# Single-LED

Distribution by DigiKey



10-4H21.1034P







## 10-4H21.1034P Single-LED

OF	'ERA	ATIN	G-/	INDI	CAT	ION	PART

Illumination colour: Yellow

#### **ELECTRICAL CHARACTERISTICS**

**Operating voltage:** 72 V AC/DC

**Operation current:** 2,2 mA -30%/+25%

**Lumi. Intensity:** 4 x 112 mcd

#### **MECHANICAL CHARACTERISTICS**

**Weight:** 0.002 kg

#### **CERTIFICATE**

**REACH:** REACH compliant

RoHS: RoHS compliant

#### OTHER

**Short Description:** Single-LED, BA9s, Yellow, 72 V AC/DC


**Kind of illlumination:** Multi-LED EN 50155

**Hints:** A suitable LED remover Part No. 700.006.0, The luminous intensity stated is for

when used with DC, Electrical and optical data are measured at 25 °C, The specified 72 and 110 VAC/VDC versions are built with a bridge rectifier, The specified case one LED fails, the other pair of still functioning LED is working. The light output then is half in order to indicate the malfunction and shows this way the need for replacement, Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination.

The customer has to decide what resistor shall be used to the LED

Wiring diagrams:



### Dimension drawings:

