

Your Expert Partner for Human Machine Interfaces

Distribution by DigiKey DigiKey



10-4H21.1035P





https://digikey.eao.com/p/10-4H21.1035P


Your product:



10-4H21.1035P Single-LED

OPERATING-/INDICATION PART	
Illumination colour:	Green
ELECTRICAL CHARACTERISTICS	
Operating voltage:	72 V AC/DC
Operation current:	2,2 mA -30%/+25%
Lumi. Intensity:	4 x 478 mcd
MECHANICAL CHARACTERISTICS	
Weight:	0.002 kg
CERTIFICATE	
REACH:	REACH compliant
RoHS:	RoHS compliant
OTHER	
Short Description:	Single-LED, BA9s, Green, 72 V AC/DC
Kind of illlumination:	Multi-LED EN 50155
Hints:	A suitable LED remover Part No. 700.006.0 The luminous intensity stated is for when used with DC Electrical and optical data are measured at 25 °C The specified 72 and 110 VAC/VDC versions are built with a bridge rectifier The specified 72 and 110 VAC/VDC versions are built with a protection diode In case one LED fails, the other pair of still functioning LED's is working. The light output then is half in order to indicate the malfunction and shows this way the need for replacement Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination. The customer has to decide what resistor shall be used to the LED

Wiring diagrams:



Dimension drawings:

