

# Actuator

18-138.035 Distribution by DigiKey









## 18-138.035 Actuator

| PRODUCT RANGE |  |
|---------------|--|
|---------------|--|

Front bezel colour:

| Product Status: | Phase-out |
|-----------------|-----------|
|                 |           |
|                 |           |
| FRONT           |           |

Black

Front dimension: Ø 9 mm
Front form: Round

Front bezel material: Plastic

**MOUNTING** 

**Design:** Raised

Mounting type: Panel mounting

**OPERATING-/INDICATION PART** 

Lens illumination: Illuminated

#### **ELECTRICAL CHARACTERISTICS**

Switching voltage and switching 100 mA at 42 VAC/VDC current:

Contacts: 1 NC

Switching rating:  $42 \lor @ 0,1 A$ 

**Electrical lifetime:** ≥500 000 cycles of operation at 30 VDC, 100 mA, according to IEC 61058-1

**Electric strength:** 500 VAC, 50 Hz, 1 minute, as per IEC 60512-2-11 between all terminals and earth

## **MECHANICAL CHARACTERISTICS**

| Terminal:              | Soldering terminal  |
|------------------------|---|
| Contact material:      | Gold  |
| Switching action:      | Momentary   |
| Switching system:      | Snap-action switching element   |
| Switching system:      | The snap-action switching system was designed for switching low powers in electronic circuits. Single-break snap-action contact.                        |
| Mechanical lifetime:   | 2 Mil. cycles of operation  |
| Operating force:       | 1.4 N   |
| Operating Travel:      | ca. 2.2 mm ± 0.2 mm   |
| Tightening torque:     | Fixing nut max. 0.2 Nm  |
| Wire cross section:    | Max. wire cross-section 2 wires with 0.5 mm Max. wire cross-section of stranded cable 1 x 0.75 mm $^2$ Wire cross-section of terminal 1,6 x 0,4 mm $^2$ |
| Weight:                | 0.002 kg  |
|                        |   |
| AMBIENT CONDITION      |   |
| IP front protection:   | IP40, according to IEC 60529  |
| Operating temperature: | – 25 °C + 65 °C   |
| Storage temperature:   | – 40 °C + 80 °C   |
| Shock resistance:      | 50 g for 11 ms, as per DIN / EN 60068-2-27 (Single impacts, semi-sinusoidal)  |
| Vibration resistance:  | 10 g at 10 Hz2000 Hz, amplitude 0.75 mm (Sinusoidal), according to DIN EN 60512-4-4   |
|                        |   |
| CERTIFICATE            |   |
| Conformities:          | 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD) for version 230 VAC   |
| REACH:                 | REACH compliant   |
| RoHS:                  | RoHS compliant  |
|                        |   |
|                        |   |

#### **OTHER**

Actuator,  $\varnothing$  9 mm, Illuminated, Round, Black, Plastic, 1 NC, Momentary, Soldering terminal, IP40, according to IEC 60529 **Short Description:** 

Internal size: Ø 7,5 mm

Black Housing colour:


Housing material:

Plastic


**Product attributes:** 

+/- terminals are not connected

Wiring diagrams:



#### **Component layouts:**




A = Terminals (rear side)

B = Illuminated pushbutton

C = x = Contact No.

D = 2 = Normally open E = 4 = Normally close

Mounting cut-outs:



## Dimension drawings:

