

Your Expert Partner for Human Machine Interfaces

Actuator

18-147.035 Distribution by DigiKey







https://digikey.eao.com/p/18-147.035

Your product:



18-147.035 Actuator

PRODUCT RANGE

Electrical lifetime:

Electric strength:

| Product Status: | Phase-out |
|--|----------------------|
| | |
| FRONT | |
| Front dimension: | 14 mm x 9 mm |
| Front form: | Rectangular |
| Front bezel colour: | Black |
| Front bezel material: | Plastic |
| | |
| MOUNTING | |
| Design: | Raised |
| Mounting type: | Panel mounting |
| | |
| OPERATING-/INDICATION PART | |
| Lens illumination: | Illuminated |
| | |
| ELECTRICAL CHARACTERISTICS | |
| Switching voltage and switching current: | 100 mA at 42 VAC/VDC |
| Contacts: | 1 NO |
| Switching rating: | 42 V @ 0,1 A |

≥500 000 cycles of operation at 30 VDC, 100 mA, according to IEC 61058-1

500 VAC, 50 Hz, 1 minute, as per IEC 60512-2-11 between all terminals and earth

MECHANICAL CHARACTERISTICS

| Terminal: | Soldering terminal |
|----------------------|---|
| Contact material: | Gold |
| Switching action: | Momentary |
| Switching system: | Snap-action switching element |
| Switching system: | The snap-action switching system was designed for switching low powers in electronic circuits. Single-break snap-action contact. |
| Mechanical lifetime: | 2 Mil. cycles of operation |
| Operating force: | 1.4 N |
| Operating Travel: | ca. 2.2 mm ± 0.2 mm |
| Tightening torque: | Fixing nut max. 0.2 Nm |
| Wire cross section: | Max. wire cross-section 2 wires with 0.5 mm Max. wire cross-section of stranded cable 1 x 0.75 mm ² Wire cross-section of terminal 1,6 x 0,4 mm ² |
| Weight: | 0.002 kg |

AMBIENT CONDITION

| IP front protection: | IP40, according to IEC 60529 |
|------------------------|---|
| Operating temperature: | – 25 °C + 65 °C |
| Storage temperature: | – 40 °C + 80 °C |
| Shock resistance: | 50 g for 11 ms, as per DIN / EN 60068-2-27 (Single impacts, semi-sinusoidal) |
| Vibration resistance: | 10 g at 10 Hz2000 Hz, amplitude 0.75 mm (Sinusoidal), according to DIN EN 60512-4-4 |

| CE | DT | 100 | 0 | λT | |
|----|----|-----|---|----------|----|
| | RT | гст | 6 | ۱ | с. |
| | | | | | |

| Conformities: | 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD) for version 230 VAC |
|---------------|---|
| REACH: | REACH compliant |
| RoHS: | RoHS compliant |

OTHER

| Short Description: | Actuator, 14 mm x 9 mm, Illuminated, Rectangular, Black, Plastic, 1 NO, Momentary, Soldering terminal, IP40, according to IEC 60529 |
|--------------------|--|
| Internal size: | 12,5 mm x 7,5 mm |
| Housing colour: | Black |


Housing material:

Plastic

Product attributes:

Wiring diagrams:

+/- terminals are not connected




(A) (B) 9 x 9 mm 19 x 19 mm 9 x 14 mm 0 9 mm 0 19 x 19 mm 0 19 x 19 mm (1 x) (1 x)

- A = Terminals (rear side)
- B = Illuminated pushbutton
- C = x = Contact No.
- D = 2 = Normally open
- E = 4 = Normally close

Mounting cut-outs:

Component layouts:



Dimension drawings:

