

Actuator

18-248.035 Distribution by DigiKey









18-248.035 Actuator

P	R	O	D	u	CI	ГΕ	ŁΔ	N	G	F

Product Status: Phase-out

FRONT

Front dimension: 14 mm x 9 mm

Front form: Rectangular

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Design: Raised

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens illumination: Illuminated

ELECTRICAL CHARACTERISTICS

Switching voltage and switching 100 mA at 42 VAC/VDC current:

Contacts: 1 NC

Switching rating: $42 \lor @ 0,1 A$

Electrical lifetime: ≥500 000 cycles of operation at 30 VDC, 100 mA, according to IEC 61058-1

Electric strength: 500 VAC, 50 Hz, 1 minute, as per IEC 60512-2-11 between all terminals and earth

MECHANICAL CHARACTERISTICS

Terminal:	Soldering terminal					
Contact material:	Gold					
Switching action:	Maintained					
Switching system:	Snap-action switching element					
Switching system:	The snap-action switching system was designed for switching low powers in electronic circuits. Single-break snap-action contact.					
Mechanical lifetime:	1 Mil. cycles of operation					
Operating force:	1.4 N					
Operating Travel:	ca. 2.2 mm ± 0.2 mm					
Tightening torque:	Fixing nut max. 0.2 Nm					
Wire cross section:	Max. wire cross-section 2 wires with 0.5 mm Max. wire cross-section of stranded cable 1 x 0.75 mm 2 Wire cross-section of terminal 1,6 x 0,4 mm 2					
Weight:	0.002 kg					
AMBIENT CONDITION						
IP front protection:	IP40, according to IEC 60529					
Operating temperature:	– 25 °C + 65 °C					
Storage temperature:	– 40 °C + 80 °C					
Shock resistance:	50 g for 11 ms, as per DIN / EN 60068-2-27 (Single impacts, semi-sinusoidal)					
Vibration resistance:	10 g at 10 Hz2000 Hz, amplitude 0.75 mm (Sinusoidal), according to DIN EN 60512-4-4					
CERTIFICATE						
Conformities:	2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD) for version 230 VAC					
REACH:	REACH compliant					
RoHS:	RoHS compliant					

OTHER

Actuator, 14 mm x 9 mm, Illuminated, Rectangular, Black, Plastic, 1 NC, Maintained, Soldering terminal, IP40, according to IEC 60529 **Short Description:**

Internal size: 12,5 mm x 7,5 mm

Black Housing colour:


Housing material:

Plastic


Product attributes:

+/- terminals are not connected

Wiring diagrams:



Component layouts:




A = Terminals (rear side)

B = Illuminated pushbutton
C = x = Contact No.

D = 2 = Normally open

E = 4 = Normally close

Mounting cut-outs:



Dimension drawings:

