

Actuator

45-2234.21E0.000 Distribution by DigiKey









45-2234.21E0.000 Actuator

Front dimension:Ø 29,5 mmFront form:RoundFront bezel colour:Silver

Metal

MOUNTING

Front bezel material:

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Red

Lens material: Plastic

Lens illumination: Illuminated

Lens shape: Flush

Lens optics: transparent

Lens type: Level with front bezel


Illumination colour: Red

MECHANICAL CHARACTERISTICS


Switching action: Maintained

Switching system: Slow-make switching element

Mechanical lifetime:	500 000 cycles of operation
Operating frequency:	Max. 1 800/h
Weight:	0.038 kg
AMBIENT CONDITION	
IP front protection:	IP66, IP67, IP69K
Operating temperature:	– 25 °C + 70 °C
Storage temperature:	– 40 °C + 80 °C
Shock resistance:	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms
Vibration resistance:	According to IEC 60068-2-6: 20 500 Hz: 5 g
Climate resistance:	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6
CERTIFICATE	
REACH:	REACH compliant
RoHS:	RoHS compliant
OTHER	
Short Description:	Actuator, \varnothing 22.3 mm, \varnothing 29,5 mm, Flush, Illuminated, Red, Plastic, transparent, Round, Silver, Metal, Maintained, IP66, IP67, IP69K, Red
Housing colour:	Silver
Housing material:	Metal
Product attributes:	Push to unlatch
Hints:	Push to unlatch
Wiring diagrams:	



Mounting cut-outs:



Dimension drawings:

