

# Actuator

45-

2631.19G0.000

Distribution by DigiKey









# 45-2631.19G0.000 Actuator

## **FRONT**

Front dimension: Ø 40 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

#### **MOUNTING**

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

## **OPERATING-/INDICATION PART**

Lens colour: Yellow

Lens material: Plastic

Lens illumination: Illuminated

Lens shape: Mushroom-head

Lens optics: transparent

## **MECHANICAL CHARACTERISTICS**

Switching action: Momentary

Switching system: Slow-make switching element

**Mechanical lifetime:** 10 Mil. cycles of operation

**Operating frequency:** Max. 3 600/h

Weight:	0.026 kg
---------	----------

#### **AMBIENT CONDITION**

**IP front protection:** IP66, IP67, IP69K

**Operating temperature:**  $-25 \, ^{\circ}\text{C} \, ... + 70 \, ^{\circ}\text{C}$ 

Storage temperature:  $-40 \,^{\circ}\text{C} \dots + 80 \,^{\circ}\text{C}$ 

**Shock resistance:** According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

**Vibration resistance:** According to IEC 60068-2-6: 20 ... 500 Hz: 5 g

Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

### **CERTIFICATE**

**REACH:** REACH compliant

**RoHS:** RoHS compliant

### **OTHER**


Short Description: Actuator, Ø 22.3 mm, Ø 40 mm, Mushroom-head, Illuminated, Yellow, Plastic,

transparent, Round, Black, Plastic, Momentary, IP66, IP67, IP69K


Housing colour: Black

Housing material: Plastic

Wiring diagrams:



## Mounting cut-outs:



# Dimension drawings:

