

# Actuator

45-2845.2E90.002 Distribution by DigiKey









# 45-2845.2E90.002 Actuator

## **FRONT**

Front dimension: Ø 29,5 mm

Front form: Round

Front bezel colour: Silver

Front bezel material: Metal

#### **MOUNTING**

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

## **OPERATING-/INDICATION PART**

Lever colour: White

Lever material: plastic

Lever shape: round

### **MECHANICAL CHARACTERISTICS**

**Switching action:** Maintained - Maintained - Maintained - Maintained

**Switching positions:** 4 positions

Mechanical lifetime: 1 Mil. cycles of operation

Operating frequency: 1 800/h

**Weight:** 0.001 kg

### **AMBIENT CONDITION**

IP front protection: IP66, IP67, IP69K

**Operating temperature:**  $-25 \, ^{\circ}\text{C} \, ... + 70 \, ^{\circ}\text{C}$ 

Storage temperature:  $-40 \, ^{\circ}\text{C} \dots + 80 \, ^{\circ}\text{C}$ 

**Shock resistance:** According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

**Vibration resistance:** According to IEC 60068-2-6: 10 ... 500 Hz: 5 g

Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

#### **CERTIFICATE**

**REACH:** REACH compliant

RoHS: RoHS compliant


#### **OTHER**

Short Description: Actuator, ∅ 22.3 mm, ∅ 29,5 mm, optional illuminative, White, round, Round,

Silver, Metal, Maintained - Maintained - Maintained - Maintained, IP66, IP67, IP69K

Housing material: Metal


Switching positions:



Wiring diagrams:

f------

Mounting cut-outs:



## Dimension drawings:

