

# Actuator

45-  
2C35.1920.110

Distribution by  
DigiKey

**DigiKey**

<https://digikey.eao.com/p/45-2C35.1920.110>

Your product:

---



## 45-2C35.1920.110 Actuator

### FRONT

Front dimension:	Ø 40 mm
Front form:	Round
Front bezel colour:	Black
Front bezel material:	Plastic

### MOUNTING

Mounting type:	Panel mounting
----------------	----------------

### OPERATING-/INDICATION PART

Lens colour:	Red
Lens material:	Plastic
Lens illumination:	Non illuminated
Lens shape:	Mushroom-head
Lens optics:	opaque

### MECHANICAL CHARACTERISTICS

Switching action:	Maintained
Release type:	Key release to unlock
Mechanical lifetime:	300 000 cycles of operation
Operating frequency:	Max. 600/h
Weight:	0.075 kg


## AMBIENT CONDITION

<b>Operating temperature:</b>	– 25 °C ... + 70 °C
<b>Storage temperature:</b>	– 40 °C ... + 80 °C
<b>Shock resistance:</b>	According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms
<b>Vibration resistance:</b>	According to IEC 60068-2-6: 2 ... 500 Hz: 5 g
<b>Climate resistance:</b>	During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6

## CERTIFICATE

<b>REACH:</b>	REACH compliant
<b>RoHS:</b>	RoHS compliant

## OTHER

<b>Short Description:</b>	Actuator, Ø 40 mm, Mushroom-head, Non illuminated, Red, Plastic, opaque, Round, Black, Plastic, Maintained, Key release to unlock
<b>Dimension:</b>	Ø 40 mm
<b>Housing colour:</b>	Yellow
<b>Housing material:</b>	Plastic
<b>Product attributes:</b>	Key release to unlock anti-clockwise
<b>Hints:</b>	Application as per DIN EN ISO 13850 and EN 60204-1
<b>Wiring diagrams:</b>	

**Mounting cut-outs:**



**Dimension drawings:**

