

Actuator

45-2F0V.1010.000 Distribution by DigiKey







Your product:



45-2F0V.1010.000 Actuator

Front dimension: Ø 29,5 mm

Front form: Round

Front bezel colour: Black

Front bezel material: Plastic

MOUNTING

Design: Raised

Mounting cut-out: Ø 22.3 mm

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lever colour: Black

Lever material: plastic

MECHANICAL CHARACTERISTICS

Switching action: Momentary

Mechanical lifetime: 250 000 cycles of operation per direction of actuation

Weight: 0.085 kg

AMBIENT CONDITION

IP front protection: IP65, IP67

Operating temperature: $-25 \, ^{\circ}\text{C} \, ... + 70 \, ^{\circ}\text{C}$

Storage temperature: $-40 \,^{\circ}\text{C} \dots + 80 \,^{\circ}\text{C}$

Shock resistance: According to IEC 60068-2-27: Sinusoidal half-wave 50 g / 11 ms

Vibration resistance: According to IEC 60068-2-6: 10 ... 500 Hz: 5 g

Climate resistance: During operation according to IEC 60721: 3K6, 3C3, 3S2, 3M6, 3B2

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER

Short Description: Actuator, Ø 22.3 mm, Ø 29,5 mm, Black, Round, Black, Plastic, Momentary, IP65,

IP67


Housing material: Plastic

Product attributes: 4 positions

Hints: Lockable only in center position

Wiring diagrams:

Mounting cut-outs:



Dimension drawings:

