

Actuator

46-
2234.31E0.000

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/p/46-2234.31E0.000>

Your product:



46-2234.31E0.000

Actuator

FRONT

Front form:	round
Front dimension:	Ø 29,5 mm
Front bezel colour:	Silver
Front bezel material:	Metal

MOUNTING

Mounting type:	Panel mounting
Design:	raised
Mounting cut-out:	Ø 22.3 mm

OPERATING-/INDICATION PART

Lens optics:	transparent
Lens shape:	flush
Lens illumination:	illuminative
Lens material:	Plastic
Lens colour:	Red

ELECTRICAL CHARACTERISTICS

Protection class:	II
--------------------------	----

MECHANICAL CHARACTERISTIC

Mechanical lifetime:	500 000 cycles of operation
-----------------------------	-----------------------------

Weight: 0.033 kg
Tightening torque: 2 ... 3 Nm (17.7 ... 26.6 Lb-in)
Switching action: Maintained

AMBIENT CONDITION

IK front protection: IK03
IP front protection: IP65
Shock resistance: 50g, 11ms (EN-IEC 60068-2-27)
Operating temperature: - 25 °C ... + 55 °C
Climate resistance: +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
Vibration resistance: 5g f= 2...500Hz (EN-IEC 60068-2-6)

CERTIFICATE

Standards: CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508
Conformities: CE

OTHER

Housing material: Plastic
Housing colour: Black
max. number of switching elements: 6

Short Description: Actuator, Ø 22.3 mm, Ø 29,5 mm, flush, illuminative, Red, Plastic, transparent, round, Silver, Metal, Maintained, IP65, IK03

Dimension drawings:

