

Actuator

46-
280S.1CV0.008

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/p/46-280S.1CV0.008>

Your product:



46-280S.1CV0.008 Actuator

FRONT

Front bezel colour:	Black
Front dimension:	Ø 29 mm
Front form:	round
Front bezel material:	Plastic

MOUNTING

Design:	raised
Mounting cut-out:	Ø 22.3 mm

OPERATING-/INDICATION PART

Lever bar colour:	White
Lever shape:	short
Lever colour:	Black
Lever material:	plastic

ELECTRICAL CHARACTERISTICS

Protection class:	II
--------------------------	----

MECHANICAL CHARACTERISTIC

Mechanical lifetime:	1 Mio. cycles of operation
Switching action:	Momentary - Rest - Momentary
Switching positions:	3 positions

Switching angle: 60° left / 60° right
Weight: 0.031 kg
Tightening torque: 2 ... 3 Nm (17.7 ... 26.6 Lb-in)

AMBIENT CONDITION

Climate resistance: +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)
IP front protection: IP65
Operating temperature: - 25 °C ... + 55 °C
IK front protection: IK06
Vibration resistance: 5g f= 2...500Hz (EN-IEC 60068-2-6)
Shock resistance: 30g, 18ms (EN-IEC 60068-2-27)
50g, 11ms (EN-IEC 60068-2-27)


CERTIFICATE

Approbations: CSA, EAC, UL
Conformities: CE
Standards: CSA G22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508


OTHER

Housing colour: Black
max. number of switching elements: 8
Housing material: Plastic
Short Description: Actuator, Ø 22.3 mm, Ø 29 mm, non illuminative, Black, short, round, Black, Plastic, Momentary - Rest - Momentary, IP65, IK06

Dimension drawings:



Switching positions:



Mounting cut-outs:

