

Actuator

46-
290J.1000.7PD

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/p/46-290J.1000.7PD>

Your product:



46-290J.1000.7PD Actuator

FRONT

Front form:	round
Front bezel colour:	Black
Front bezel material:	Plastic
Front dimension:	Ø 29 mm

MOUNTING

Design:	raised
Mounting cut-out:	Ø 22.3 mm

ELECTRICAL CHARACTERISTICS

Protection class:	II
--------------------------	----

MECHANICAL CHARACTERISTIC

Mechanical lifetime:	50 000 cycles of operation
Switching action:	Maintained (a) - Maintained
Tightening torque:	2 ... 3 Nm (17.7 ... 26.6 Lb-in)
Switching angle:	120°
Switching positions:	2 positions
Weight:	0.08 kg

AMBIENT CONDITION

IP front protection:	IP65
-----------------------------	------

Operating temperature: - 25 °C ... + 55 °C

IK front protection: IK06

Vibration resistance: 5g f= 2...500Hz (EN-IEC 60068-2-6)

Shock resistance: 30g, 18ms (EN-IEC 60068-2-27)
50g, 11ms (EN-IEC 60068-2-27)

Climate resistance: +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)

CERTIFICATE

Standards: CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508

Conformities: CE

Approbations: CSA, EAC, UL

OTHER


max. number of switching elements: 8

Housing material: Plastic


Short Description: Actuator, Ø 22.3 mm, Ø 29 mm, round, Black, Plastic, Maintained (a) - Maintained, IP65, IK06

Housing colour: Black

Mounting cut-outs:



Switching positions:



Dimension drawings:

