

Actuator

46-
2W0S.1CN0.004

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/p/46-2W0S.1CN0.004>

Your product:



46-2W0S.1CN0.004 Actuator

FRONT

Front dimension:	Ø 30 mm
Front bezel colour:	Black
Front form:	round
Front bezel material:	Plastic

MOUNTING

Mounting cut-out:	Ø 22.3 mm
Design:	raised

OPERATING-/INDICATION PART

Lever shape:	short
Lever colour:	White
Lever bar colour:	White
Lever material:	plastic

ELECTRICAL CHARACTERISTICS

Protection class:	II
--------------------------	----

MECHANICAL CHARACTERISTIC

Switching angle:	45° left / 45° right
Switching positions:	3 positions
Switching action:	Momentary - Rest - Momentary

Tightening torque: 2 ... 3 Nm (17.7 ... 26.6 Lb-in)
Weight: 0.027 kg
Mechanical lifetime: 1 Mio. cycles of operation

AMBIENT CONDITION


Operating temperature: - 25 °C ... + 55 °C
Vibration resistance: 5g f= 2...500Hz (EN-IEC 60068-2-6)
Shock resistance: 30g, 18ms (EN-IEC 60068-2-27)
IK front protection: IK03
IP front protection: IP65
Climate resistance: +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)

CERTIFICATE


Conformities: CE
Standards: CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508

OTHER

Short Description: Actuator, Ø 22.3 mm, Ø 30 mm, illuminative, White, short, round, Black, Plastic, Momentary - Rest - Momentary, IP65, IK03
Housing material: Plastic
max. number of switching elements: 2
Housing colour: Black
Switching positions:



Dimension drawings:



Mounting cut-outs:

