

Switching element

46-311.1X10

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/p/46-311.1X10>

Your product:



46-311.1X10 Switching element

FRONT

Colour: Green

ELECTRICAL CHARACTERISTICS

Contacts: 1 NO

Pollution degree: 3

Insulation voltage: Ui 690V - Uimp 4KV (IEC-EN60947-1)

Thermal current Ith: 10 A (IEC-EN60947-1)

Switching voltage and switching current:

at AC-15				
Voltage	24 V	120 V	240 V	600 V
Current	10 A	6 A	3 A	1,2 A
at DC-13				
Voltage	24 V	120 V	240 V	
Current	5 A	1,1 A	0,55 A	

MECHANICAL CHARACTERISTIC

Switching system: Slow-make switching element

Tightening torque: 0.8 ... 1 Nm for screw terminal

Operating force: 2 N

Weight: 0.01 kg

Mechanical lifetime: 1 Mio. cycles of operation

Contact material: Gold-plated silver

Terminal: Screw terminal

AMBIENT CONDITION

Operating temperature: - 25 °C ... + 55 °C

Vibration resistance: 5g f= 2...500Hz (EN-IEC 60068-2-6)

IP Protection: IP20

Shock resistance: 30g, 18ms (EN-IEC 60068-2-27)
50g, 11ms (EN-IEC 60068-2-27)

Climate resistance: +25°C-97%RH / +45°C-93%RH (IEC-EN60068-2-30)

CERTIFICATE

Standards: CSA C22-2, IEC EN 60947-1, IEC EN 60947-5-1, UL508

Conformities: CE


Approbations: CSA, EAC, UL

OTHER

Material: Plastic

Short Description: Switching element, Slow-make switching element, Gold-plated silver, 1 NO, Screw terminal

Wiring diagrams:



Dimension drawings:

