

e a o

Your Expert Partner for Human Machine Interfaces

Actuator

Distribution by
DigiKey

DigiKey

704.006.6



<https://digikey.eao.com/component/704.006.6/e...>

Your product:



704.006.6
Actuator

FRONT

Front dimension:	Ø 29 mm
Front form:	Round
Front bezel colour:	Black
Front bezel material:	Plastic

MOUNTING

Design:	Raised
Mounting type:	Panel mounting

OPERATING-/INDICATION PART

Lens colour:	Blue
Lens material:	Plastic
Lens shape:	Flush
Lens optics:	transparent
Marking plate colour:	White
Marking plate optics:	translucent
Marking plate illumination:	illuminative

ELECTRICAL CHARACTERISTICS

Standards:	The switches comply with the "Standards for low-voltage switching devices" DIN EN 60947-1
-------------------	---

MECHANICAL CHARACTERISTICS

Terminal: Screw terminal

Weight: 0.037 kg

AMBIENT CONDITION

IP Protection: IP65 front side

Operating temperature: – 40 °C ... + 55 °C

Storage temperature: – 40 °C ... + 85 °C

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER

Short Description: Actuator, Ø 29 mm, Flush, Blue, Plastic, transparent, Round, Black, Plastic, Screw terminal


Housing colour: Grey

Housing material: Plastic

Hints: Filament lamp or LED



Wiring diagrams:

X2+



X1-

Mounting cut-outs:



A = Screw terminal

B = Push-in terminal (PIT)

Dimension drawings:

A = Screw terminal

