


Actuator

704.066.2

Distribution by
DigiKey

DigiKey



<https://digkey.eao.com/component/704.066.2/e...>

Your product:



704.066.2 Actuator

Loading ...

FRONT

Front dimension: Ø 37 mm

Front form: Round

MOUNTING

Design: Raised

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lens colour: Red

Lens material: Plastic

Lens illumination: Non illuminated

Lens shape: Mushroom-head

Lens optics: opaque

ELECTRICAL CHARACTERISTICS

Standards: The switches comply with the "Standards for low-voltage switching devices" DIN EN 60947-1

MECHANICAL CHARACTERISTICS

Switching action: Maintained

Release type: Key release to unlock

Mechanical lifetime: ≤50 000 cycles of operation

Operating force: 8 N

Operating Travel: ca. 5.8 mm ± 0.2 mm
Weight: 0.077 kg

AMBIENT CONDITION

IP Protection: IP65 front side
Operating temperature: – 40 °C ... + 55 °C
Storage temperature: – 40 °C ... + 85 °C


CERTIFICATE

REACH: REACH compliant
RoHS: RoHS compliant

OTHER

Short Description: Actuator, Ø 37 mm, Mushroom-head, Non illuminated, Red, Plastic, opaque, Round, Maintained, Key release to unlock
Housing colour: Yellow
Housing material: Plastic
Marking: Arrows
Product attributes: Key to unlock clockwise
Hints: Shaft yellow
max. number of switching elements: 2

Wiring diagrams:



Mounting cut-outs:

