

Actuator

704.101.0

Distribution by DigiKey







Your product:



704.101.0 Actuator

FRONT	
Front dimension:	Ø 29 mm
Front form:	Round
Front bezel colour:	Nature
Front bezel material:	Aluminium
MOUNTING	
Design:	Raised
Mounting type:	Panel mounting
OPERATING-/INDICATION PART	
Lever colour:	Black
Lever bar colour:	Black
Lever material:	plastic
Lever shape:	long
ELECTRICAL CHARACTERISTICS	
Standards:	The switches comply with the "Standards for low-voltage switching devices" DII EN 60947-1
MECHANICAL CHARACTERISTICS	

Switching action: Rest - Maintained

Switching positions: 2 positions


Switching angle: $90^{\circ} \text{ right } / -45^{\circ} \dots +45^{\circ}$

Mechanical lifetime: ≤2.5 Mil. o	cycles of operation
Weight: 0.036 kg	
AMBIENT CONDITION	
IP Protection: IP65 front	side
Operating temperature: - 40 °C	+ 55 °C
Storage temperature: - 40 °C	+ 85 °C
CERTIFICATE	
REACH: REACH co	mpliant
RoHS: RoHS com	pliant
OTHER	
Short Description: Actuator, anodised,	ð 29 mm, non illuminative, Black, long, Round, Nature, Aluminium, Rest - Maintained
Hints: Max. 3 sw	itching elements can be clipped on
max. number of switching 3 elements:	
Switching positions:	
0	
	X
1	

Wiring diagrams:




Mounting cut-outs:



A = Screw terminal

B = Push-in terminal (PIT)
C = Plug-in terminal 6.3 mm x 0.8 mm
D = Double plug-in terminal 6.3 mm x 0.8

Dimension drawings:



A = Screw terminal