

# Actuator

704.120.018

Distribution by DigiKey









## 704.120.018 Actuator

		$\sim$		_
-	к	( )	N	
		v		

Front dimension: Ø 35 mm

Front form: Round

Front bezel colour: Nature

Front bezel material: Aluminium

#### **MOUNTING**

Design: Flush

Mounting cut-out: Ø 30.5 mm

Mounting type: Panel mounting

#### **ELECTRICAL CHARACTERISTICS**

Standards: The switches comply with the "Standards for low-voltage switching devices" DIN

EN 60947-1

#### **MECHANICAL CHARACTERISTICS**

Switching action: Rest - Maintained (a)

**Switching positions:** 2 positions

**Switching angle:**  $90^{\circ} \text{ right / -}45^{\circ} \dots +45^{\circ}$ 


**Mechanical lifetime:** ≤50 000 cycles of operation

**Weight:** 0.103 kg

#### **AMBIENT CONDITION**


**IP Protection:** IP65 front side

Operating temperature:	– 40 °C + 55 °C		
Storage temperature:	– 40 °C + 85 °C		
CERTIFICATE			
REACH:	REACH compliant		
RoHS:	RoHS compliant		
OTHER			
Short Description:	Actuator, Ø 30.5 mm, Ø 35 mm, Round, Nature, Aluminium, Rest - Maintained (a)		
	The standard lock Ronis 251 Further lock numbers on request Max. 3 switching elements can be clipped on		
Hints:	Further lock numbers on request		
max. number of switching elements:	Further lock numbers on request		
max. number of switching	Further lock numbers on request Max. 3 switching elements can be clipped on		
max. number of switching elements:	Further lock numbers on request Max. 3 switching elements can be clipped on		
max. number of switching elements:	Further lock numbers on request Max. 3 switching elements can be clipped on		



Wiring diagrams:		
	8-~-	-~-


Mounting cut-outs:



A = Screw terminal

B = Push-in terminal (PIT)
C = Plug-in terminal 6.3 mm x 0.8 mm
D = Double plug-in terminal 6.3 mm x 0.8

### **Dimension drawings:**



A = Screw terminal