

Actuator

704.408.0

Distribution by DigiKey







Your product:



704.408.0 Actuator

FRONT	
Front dimension:	Ø 29 mm
Front form:	Round
Front bezel colour:	Grey
Front bezel material:	Plastic
MOUNTING	
Design:	Raised
Mounting type:	Panel mounting
OPERATING-/INDICATION PART	
Lever colour:	Black
Lever bar colour:	White
Lever material:	plastic
Lever shape:	short
ELECTRICAL CHARACTERISTICS	
Standards:	The switches comply with the "Standards for low-voltage switching devices" DIN EN 60947-1
	LIN 00047 I
MECHANICAL CHARACTERISTICS	

Momentary - Rest - Maintained Switching action:

Switching positions: 3 positions

Switching angle: 42° left / 42° right **Mechanical lifetime:** ≤2.5 Mil. cycles of operation

Weight: 0.029 kg

AMBIENT CONDITION

IP Protection: IP65 front side

Operating temperature: $-40 \, ^{\circ}\text{C} \, ... + 55 \, ^{\circ}\text{C}$

Storage temperature: $-40 \, ^{\circ}\text{C} \dots + 85 \, ^{\circ}\text{C}$

CERTIFICATE

REACH: REACH compliant

RoHS: RoHS compliant

OTHER

Short Description: Actuator, ∅ 29 mm, non illuminative, Black, short, Round, Grey, Plastic,

Momentary - Rest - Maintained


Hints: Max. 3 switching elements can be clipped on

max. number of switching

elements:

3


Switching positions:



Wiring diagrams:

F--- ---


Mounting cut-outs:



A = Screw terminal

B = Push-in terminal (PIT)
C = Plug-in terminal 6.3 mm x 0.8 mm
D = Double plug-in terminal 6.3 mm x 0.8

Dimension drawings:



A = Screw terminal