

Actuator

71-642.0A

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/p/71-642.0A>

Your product:



71-642.0A

Actuator

MOUNTING

Mounting type: Panel mounting

OPERATING-/INDICATION PART

Lever material: plastic

Lever shape: short

ELECTRICAL CHARACTERISTICS

Switching voltage and switching current:	Switch rating AC cosφ 0,7 ... 0,8		
	gemäss EN IEC 60947-5-1		
	Voltage	250 VAC	
	Current	3 A	
	Switch rating DC		
	gemäss EN IEC 60947-5-1		
	Voltage	24 VDC	250 VDC
	Current	3 A	0.5 A
Surge voltage resistance:	2500 VAC, 50 Hz, 1 minute, as per DIN / IEC 60512-2 between all terminals and earth		
Recommended minimum operational data:	Voltage	5 VAC/DC	
	Current	10 mA	

MECHANICAL CHARACTERISTICS

Switching action:	Rest - Maintained
Switching system:	Self-cleaning, double-break snap action switching system, 1 normally closed and 1 normally open contact per element.
Switching positions:	2 positions
Switching angle:	90° right
Mechanical lifetime:	100 000 cycles of operation
Tightening torque:	Fixing nut max. 0.5 Nm

Weight: 0.003 kg

AMBIENT CONDITION

IP Protection: IP65 front side

Operating temperature: – 25 °C ... + 55 °C

Storage temperature: – 40 °C ... + 85 °C

Shock resistance: Max. 500 m/s², pulse width, 3-axis (sinusoidal EN IEC 60068-2-27)

Vibration resistance: Max. 100 m / s² from 10 Hz ... 500 Hz, (sinusoidal EN IEC 60068-2-6)

Climate resistance: Damp heat, steady: 56 days, + 40 °C/93 % relative humidity, according to EN IEC 60068-2-78

CERTIFICATE

Conformities: CE, UKCA, 2011 / 65 / EC (RoHS), 2014 / 35 / EU (LVD)

REACH: REACH compliant

RoHS: RoHS compliant


OTHER

Short Description: Actuator, optional illuminative, short, Rest - Maintained


Housing material: Plastic, according to UL 94 V0

Hints: Pitch of the front plate mounting holes must agree with the printed circuit board holes Ø 3.5 mm



Switching positions:



Wiring diagrams:



Mounting cut-outs:



Dimension drawings:

