

# Capacitive sensor switch with IO-Link Stainless Steel

Distribution by DigiKey



84-ADKS-B11-04AB







# 84-ADKS-B11-04AB Capacitive sensor switch with IO-Link Stainless Steel

E	D	0	N	٦
	ı١	v	14	

Front dimension: Ø 30 mm

Front form: Round

Front bezel material: Stainless steel 316L

#### **MOUNTING**

Design: Flush

**Mounting cut-out:** Ø 22.5 mm

Mounting type: Panel mounting

#### **OPERATING-/INDICATION PART**

Lens material: Plastic

Lens illumination: Illuminated

Lens shape: Flush

Lens optics: transparent

**Symbol:** STOP (B11)

#### **ELECTRICAL CHARACTERISTICS**

**Operating voltage:** 8.4 - 32 V DC

Communication interface: IO-Link specification

#### **MECHANICAL CHARACTERISTICS**

**Terminal:** Connector M12

Switching system: Capacitive

**Operating force:**No actuating force necessary

**Weight:** 0.015 kg

#### **AMBIENT CONDITION**

IP front protection: IP69K

IK front protection: IK08

Operating temperature:  $-30 \, ^{\circ}\text{C} \dots + 65 \, ^{\circ}\text{C}$ 

Climate resistance: Relative humidity, max. 95%, non-condensing

#### **CERTIFICATE**

**Approbations:** CSA, EHEDG

Conformities: CE, UKCA

**REACH:** REACH compliant

RoHS: RoHS compliant

#### **OTHER**

Short Description: Capacitive sensor switch with IO-Link Stainless Steel, Ø 22.5 mm, Ø 30 mm,


Flush, Illuminated, Plastic, transparent, Round, Stainless steel 316L, Connector


M12, IP69K, IK08, STOP (B11)


Housing colour: Black

Housing material: Plastic


Wiring diagrams:










#### **Component layouts:**







## Mounting cut-outs:



### Dimension drawings:

