

Single- LED

10-2K19.1056

Distribution by
DigiKey

DigiKey



<https://digikey.eao.com/p/10-2K19.1056>

Your product:



10-2K19.1056

Single-LED

OPERATING-/INDICATION PART

Illumination colour: Blue

ELECTRICAL CHARACTERISTICS

Lumi. Intensity: 400 mcd

Operating voltage: 48 V AC/DC +10%

Operation current: 4 - 8,00 mA \pm 15 %

MECHANICAL CHARATERISTIC

Weight: 0.002 kg

OTHER


Short Description: Single-LED, T6.9, Blue, 48 V AC/DC +10%

Hints: Order two LEDs, For LED element fitting information see Application guidelines, LED polarity, Due to high surface temperatures, the series resistor must not be soldered directly to the terminals of the equipment (use a terminal plate), When using AC/DC types with AC operation, slight flickering can occur, The luminous intensity stated is for when used with DC, Electrical and optical data are measured at 25 °C, The specified versions are built with a protection diode (half wave rectifier) in series and the LED, Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination., Where supply voltages are over 48 V, a voltage-reduction element (external protective series resistor) must be used.

Kind of illumination: Single-LED

Wiring diagrams:

x2+



x1-

Dimension drawings:

