

Your Expert Partner for Human Machine Interfaces

Distribution by DigiKey DigiKey



10-4H21.1032P





https://digikey.eao.com/p/10-4H21.1032P

## Your product:



## 10-4H21.1032P Single-LED

Illumination colour:	Red
ELECTRICAL CHARACTERISTICS	
Operating voltage:	72 V AC/DC
Lumi. Intensity:	4 x 128 mcd
Operation current:	2,2 mA -30%/+25%
MECHANICAL CHARATERISTIC	
Weight:	0.002 kg
OTHER	
Kind of illlumination:	Multi-LED EN 50155
Hints:	A suitable LED remover Part No. 700.006.0, The luminous intensity stated is for when used with DC, Electrical and optical data are measured at 25 °C, The specified 72 and 110 VAC/VDC versions are built with a bridge rectifier. The specase one LED fails, the other pair of still functioning LED, s is working. The light output then is half in order to indicate the malfunction and shows this way the need for replacement, Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illuminatio The customer has to decide what resistor shall be used to the LED
Short Description:	Single-LED, BA9s, Red, 72 V AC/DC
Wiring diagrams:	x2(+) AC/DC x1(-)

Dimension drawings:

