

# Single-LED

Distribution by DigiKey



10-4H22.1034P







## 10-4H22.1034P Single-LED

<b>OPER</b>	<b>ATING</b>	-/INDIC	ATION	<b>PART</b>
-------------	--------------	---------	-------	-------------

Illumination colour: Yellow

#### **ELECTRICAL CHARACTERISTICS**

**Lumi. Intensity:** 4 x 128 mcd

Operating voltage: 110 V AC/DC

**Operation current:** 2 mA -30%/+25%

#### **MECHANICAL CHARATERISTIC**

**Weight:** 0.002 kg

#### **OTHER**

**Short Description:** Single-LED, BA9s, Yellow, 110 V AC/DC


**Kind of illlumination:** Multi-LED EN 50155

Hints: A suitable LED remover Part No. 700.006.0, The luminous intensity stated is for

when used with DC, Electrical and optical data are measured at 25 °C, The specified 72 and 110 VAC/VDC versions are built with a bridge rectifier, The specified case one LED fails, the other pair of still functioning LED is working. The light output then is half in order to indicate the malfunction and shows this way the need for replacement, Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination.

The customer has to decide what resistor shall be used to the LED

Wiring diagrams:



### Dimension drawings:

