

Your Expert Partner for Human Machine Interfaces

Distribution by DigiKey DigiKey



10-4H22.1035P





https://digikey.eao.com/p/10-4H22.1035P


Your product:



10-4H22.1035P Single-LED

| OPERATING-/INDICATION PART | |
|-----------------------------------|--|
| Illumination colour: | Green |
| | |
| ELECTRICAL CHARACTERISTICS | |
| Operation current: | 2 mA -30%/+25% |
| Operating voltage: | 110 V AC/DC |
| Lumi. Intensity: | 4 x 510 mcd |
| | |
| MECHANICAL CHARATERISTIC | |
| Weight: | 0.002 kg |
| | |
| OTHER | |
| Kind of illlumination: | Multi-LED EN 50155 |
| Short Description: | Single-LED, BA9s, Green, 110 V AC/DC |
| Hints: | A suitable LED remover Part No. 700.006.0, The luminous intensity stated is for when used with DC, Electrical and optical data are measured at 25 °C, The specified 72 and 110 VAC/VDC versions are built with a bridge rectifier, The specifier case one LED fails, the other pair of still functioning LED is is working. The light output then is half in order to indicate the malfunction and shows this way the need for replacement, Luminosity and wave length variations caused by LED manufacturing processes may cause slight differences regarding the illumination. |

Wiring diagrams:



The customer has to decide what resistor shall be used to the LED

Dimension drawings:

